

Non-Addressable Audible Visual Alarm Devices

Sounder Beacons EN54-23 Approved VADs

Honeywell's Non-Addressable Sounder Beacon is ideal for applications where a dual purpose audible and visual alarm device is required. The product features a new folded horn design, high output LEDs, advanced optics and an innovative lens design, providing outstanding sound output and omni-directional light coverage at low current draw. Specifically designed and approved to meet both EN54-3 and EN54-23, the Sounder Beacon delivers outstanding quality, reliability and extended operational life.



FEATURES & BENEFITS

Simple, Fast, Flexible Installation

- Omni-directional light coverage eliminates need for device orientation.
- Deep base option with multiple cable entries for flexible installation.
- Designed with full range of common fixing centres.
- Positive fit engagement and feedback of base with device for easy installation.

Outstanding Performance

- Approved to EN54-3 and EN54-23, C & W categories.
- 32 tones all approved to EN54-3.
- Advanced optics ensure superior light coverage.
- Synchronised flash exceeds EN54-23 standard.
- Choice of white or red light flash options.
- Soft start feature reduces power surges during system start-up.

Quality & Reliability

- Independently approved to all required standards:
 - >>Manufacturing: Construction Products Regulation (CPR)
 - >>Product performance: Light output: EN54-23 C & W categories; Sound output: EN54-3.
- Environmental: RoHS, WEEE.

Universal Device


- Tailor made range; selection according to EN54-23 C & W categories.
- Suitable for wall and ceiling mount applications.
- Global tone set: 32 tones including a new bell tone.
- Range of installation and base options, for indoor and applications up to IP65.
- Operates on 12V and 24V systems, making the range suitable for use in fire & security applications.



The requirements of EN54-23

A cube or cylinder of light with a minimum of 0.4 Lumens/m²

* X & Y dimensions are defined by the device manufacturer



Sounder Beacons Technical Specifications


Introducing the Range

DEVICE	APPROVALS		BODY COLOUR		FLASH COLOUR		LENS COLOUR	ENVIRONMENT COMPLIANCE
	EN54-23	EN54-3	RED	WHITE	RED	WHITE	CLEAR	
Sounder Beacon	W & C Class	✓	✓	✓	✓	✓	✓	RoHS/WEEE

Technical Specifications

ELECTRICAL	
Operating Voltage	12 to 29VDC
Operating Voltage Approved	EN54-23 @12 to 29 VDC (C & W) EN54-3 @ 9-14 VDC & 18-29VDCt
Current Consumption, Average	49mA @ 29VDC (W Class) Tone 7
ENVIRONMENTAL	
Operating Temperature	-25°C to 70°C
Relative Humidity	93% ±3% non condensing
Ingress Protection	IP21C – low profile base IP65 – deep base
MECHANICAL	
Body Colour	Red / White
Sound Output, Maximum	107db(A) @1m (Tone 23)t
Number of Tones	32 includes a bell tone (Full tone table available on website & manual installation)
Volume Setting	High or medium
Cable Termination Size	0.5-2.5mm ²
Material Lens / Body	Flame retardant PC/ABS
Gross Weight – Standard device	(low profile) 271g (deep / IP65) 280g
Gross Weight – First Fix option	(low profile) 283g (deep / IP65) 293g

Dimensions



Sounder Beacons Technical Specifications

Wiring Options



Product Performance

BEACON	WALL MOUNT W CLASS	WALL MOUNT W CLASS	CEILING MOUNT C CLASS	CEILING MOUNT C CLASS
Flash Colour	White	Red	White	Red
EN54-23 coverage volume code	W-2.4-8.9	W-2.4-6.2	C-3-10 / C-6-10	C-3-8.9 / C-6-8.2
Installation height (X)	2.4m max	2.4m max	3m / 6m	3m / 6m
EN54-23 coverage (Y)	Cube YY = 9.0m	Cube YY = 6.2m	Cylinder Ø = 9.5m	Cylinder Ø = 9.4 / 8.6m
EN54-23 coverage volume	190m ³	86m ³	236m ³ / 471m ³	187m ³ / 317m ³
Flash rate	0.5 Hz	0.5 Hz	0.5 Hz	0.5 Hz
Operating voltage range	12 to 29 V	12 to 29V	12 to 29V	12 to 29V
Synchronisation	Synchronisation – Automatically on power on, meets EN54-3 and exceeds EN54-23 standard			

Accessories

LOW PROFILE BASES	DEEP BASES	IP AND EARTHING KITS
CSR – Red low profile base, pack of 5	CWR – Red deep / IP65 base, pack of 5	PS189 – Deep base gasket, pack of 5
CSW – White low profile base, pack of 5	CWR – White deep / IP65 base, pack of 5	PS188 – Deep base O Ring, pack of 5
		SC076 – Earth strap, pack of 5

PRODUCT RANGE	
CWSS-RW-S5	Red body with white flash EN54-Pt.3 and Pt.23 W and C class approved sounder strobe with clear lens. Low profile base included.
CWSS-RW-W5	Red body with white flash, IP65 deep base, EN54-Pt.3 and Pt.23 W and C class approved sounder strobe with clear lens. Deep base included.
CWSS-RR-S5	Red body with red flash EN54-Pt.3 and Pt.23 W and C class approved sounder strobe with clear lens. Low profile base included.
CWSS-RR-W5	Red body with red flash, IP65 deep base, EN54-Pt.3 and Pt.23 W and C class approved sounder strobe with clear lens. Deep base included.
CWSS-WW-S5	White body with white flash EN54-Pt.3 and Pt.23 W and C class approved sounder strobe with clear lens. Low profile base included.
CWSS-WW-W5	White body with white flash, IP65 deep base, EN54-Pt.3 and Pt.23 W and C class approved sounder strobe with clear lens. Deep base included.

Honeywell

140 Waterside Road
Hamilton Industrial Park
Leicester
LE5 1TN
Tel: +44 (0) 116 246 2000
Fax: +44 (0) 116 246 2300
www.honeywell.com

SB EN54-23 | Rev 1 MB | 03/16
© 2016 Honeywell International Inc.

Honeywell